

## Declaration of Performance



- 1. Unique identification code of the product type:**  
TT40 – TT40R – TT40S – TT40W  
Roomheater burning solid fuel without hot water supply
- 2. Type batch or serial number of construction product:**  
TT40: S01-510/511                      TT40R: S01-514/515  
TT40W: S01-518/519                    TT40S: S01-520/521/522
- 3. Intended use of the construction product:**  
Roomheater burning solid fuel without hot water supply
- 4. Name and address of the manufacturer:**  
TermaTech A/S, Gunnar Clausens Vej 36, 8260 Viby J., Denmark  
Email: [info@termatech.com](mailto:info@termatech.com)    Web : [www.termatech.com](http://www.termatech.com)    Tel. : +45 8742 0035
- 5. Name and address of the authorized representative:**  
Not relevant
- 6. System of assessment and verification of constancy og performance of the construction product (AVCP)**  
System 3
- 7. Task(s) of notified body/bodies, if relevant:**  
Rhein-Ruhr Feuerstätten Prüfstelle GmbH, notified body number 1625 performed the determination of the product type on the basis of type testing  
EN 13240:2001 + A2:2004 under system 3 and issued test report no.  
40 07 1444 (TT40 + TT40R) 40 09 2136 (TT40S) 40 11 2863 (TT40W)
- 8. Declared performance**

Harmonized technical specification	EN 13240:2001 + A2:2004
<b>Essential characteristics</b>	<b>Performance</b>
<b>Fire Safety</b>	
Reaction to fire	AI
Distance to combustible materials	Minimum distances, in mm Rear: 100mm Sides: 200mm Other safety distances according to the installation instructions
Risk of burning fuel falling out	Pass
Emission of combustion products	CO: 0,08% NOx: 102 mg/m <sup>3</sup> THC: 44 mg/m <sup>3</sup> PM: 37 mg/m <sup>3</sup>
Surface temperature	Pass
Electrical safety	Pass
Cleanability	Pass
Maximum water operation pressure	- bar
Flue gass temperature at nominal heat output	324 °C
Mechanical resistance (to carry a chimney/flue)	NPD
<b>Thermal output</b>	
Nominal heat output	5 kW
Room heating output	5 kW
Water heating output	- kW
Energy efficiency	79,7%

- 9.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.  
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

15.07.2013

Søren Toft